

4 Cylinder Class Rules

- 1) **No reinforcements of any kind except** what is within the rules stated hereafter and is only for **4 cylinder class**.
- 2) 4 cylinder compact size stock hardtop automobile or station wagons allowed. You may use foreign cars, and front wheel drive automobiles. **No trucks, Jeeps, off road vehicles, rear engine, or mid-engine automobiles are allowed.** Maximum wheelbase of 106 inches, minimum wheelbase of 89 inches will be allowed. If your vehicle is all wheel drive you must disable either the front or rear drivetrain(can only be two wheel drive.) No mini subcompacts or micro vehicles or amc pacers will be allowed.
- 3) **No reinforcements of any kind will be allowed.** Only exception will be driver side front and passenger door reinforcement bars or plates added to the driver and passenger side doors may not exceed eight inches(8) past the vertical seams of the door. You may insert a dash bar maximum of 2 ½ inches in diameter from A pillar to A pillar if the dash is removed. You may use a seat bar from B pillar to B pillar maximum 2 ½ inches in diameter if you use a seat bar **you must wear a neck brace to prevent whip lash.** Trailer hitchces or any other type of stiffening devices are considered reinforcements and must be removed. You may weld rear ends or differentials to create a positive traction rear end. Rear ends can not be chained. No mini truck rear ends. No solid shocks or adding extra clamps or springs to suspension(**suspension must work freely.**) We will be permitting bumper swaps. **However you can not swap bumpers with full size vehicles(trucks, vans, ect.)** You may use factory 4 cylinder and 6 cylinder bumpers from any american made front wheel drive vehicles. When mounting bumpers to the vehicles you are allowed to weld plates to the frame horns of the vehicle and bumper being mounted. Plates are not to exceed 6 inches by 6 inches. **Do not weld bumpers onto vehicles you can mount them with ½ inch diameter bolts and a maximum of 4 bolts per mount. Mounting steel tubing or angle can not exceed no more than 3 inches into the frame rails of the vehicles and can not exceed a thickness or ¼ inch! Bumpers must be able to be unbolted from the vehicle. Do not permanently weld the bumper.** Maximum bumper height 20 inches from the ground to the center of the bumper. It is a suggestion that you may attach two vertical rods or chains approximately 12 inches from each side of the windshield opening to protect the driver from the hood coming off and collapsing into the drivers compartment.

All classes must adhere to all driver entry rules and participation regulations.