MINI PICK-UPS & MINI S U V'S Rules & Regulations Stoney Roberts Promotions, Inc. Columbia Co. Fair Thurs. Sept. 1st 6:30 P.M. \$400.00 GUARANTEED PURSE AND TROPHIES FOR SPECIALTY HEAT

RULES AND REGULATIONS

A. EACH DRIVER MUST FILL OUT AN ENTRY BLANK.

B. ALL RULES AND REGULATIONS MUST BE OBSERVED.
Track operators or promoter reserves the right to approve or reject any and all entries.

C. ALL OTHER Goshen Stampede DEMO EVENT DRIVER ENTRY, PARTICIPATION RULES, VEHICLE SET- UP RULES, AND SAFETY RULES SHALL APPLY TO THIS EVENT.

FOR MORE INFORMATION OR QUESTIONS CALL TOLL FREE 1-865-382-1955

DRIVERS ENTRY

- 1. DRIVERS MUST BE 18 YEARS OF AGE and have a valid driver's license in their possession.(16 years of age with a notarized parental medical statement obtained from Stoney Roberts Headquarters.)
- 2. ALL DRIVERS MUST SUPPLY THEIR OWN VEHICLES. You are permitted one Mini Pickup or Mini S U V per driver...
- 3. PARTICIPANTS ARE REQUIRED TO SIGN A RELEASE AND WAIVER OF LIABILITY AND INDEMNITY AGREEMENT BEFORE ENTERING ANY RESTRICTED AREA.
- 4. ENTER EARLY! Drivers may enter all sessions. <u>Upon payment of entry fee</u>, and receipt of your entry blank, you will be <u>assigned a vehicle</u> <u>number</u>. You must paint the number authorized you on your front driver, and passenger doors in 24" inch letter size. Do this only after being issued an Authorized Vehicle Number.

PARTICIPATION REGULATIONS

- 1. Mini Pickups & Mini S U V's 4 & 6 Cyl. will compete in one specialty heat.

 Mini Pickups combined S U V's will have their own Cash purse of \$400.00 each.

 No Snub Nose Trucks. Stock Mini trucks may be two or four door with extended cab. Trucks & S U V's vehicles can be equipped with four wheel, or all wheel drive.
- 2. ALL GLASS AND CHROME TRIM and anything that might become imbedded in the track, must be removed from the vehicles before bringing to the grounds. Also, trucks must be cleaned out, including beds. Do not leave broken glass in doors, clean & vacuum them out. WINDSHIELDS MUST BE REMOVED.
- 3. TIRES MUST BE STOCK SIZE, no inner liner, no wire spoked rims. Tires can only be filled with air, no fluids or solids. (tires within a tire are considered reinforcements) (tires marked tubeless may have tubes inserted in them) Remove all wheel balance weights.

 Mini Pickups & Mini SUV's Four Wheel Drive or All Wheel Drive may have up to 8 Ply tires.
- 4. A MAXIMUM OF FIVE (5) GALLONS OF GASOLINE WILL BE ALLOWED. GAS TANKS behind the axle must be moved. No Original Gas tanks will be allowed in the drivers compartments. If a substitute fuel cell or gas tank is in drivers compartment the tanks must be completely covered by a Metal firewall. If gas tanks are located in front of the rear axle and inside of frame rails they can be left in place but should be covered with a skid plate (between ground and tank) to prevent them from being damaged from the ground side. Mini Pickups GAS TANKS must be moved to truck bed just aft of the rear window, or in the case of an extended, four door cab it can be located in the back seat area if properly covered by a metal firewall. Trucks with tanks located inside the frame mid vehicle can be left but should be covered with a skid plate to help protect being punctured from track side. Only unleaded gasoline with a maximum octane level of 93 will be permitted. BOOSTED or RACING FUEL will not be allowed. If you have a vehicle equipped with a fuel pump in the gas tank, you must install a emergency cut off switch upon the dash with a red circle painted around it. No fuel pumps will be allowed within the driver's compartment. If you run gas lines in the drivers compartment they must be double lined & double clamped. (a fuel line within another line.)
- 5. ONLY ONE (1) STOCK BATTERY will be allowed. A maximum of 1200 cold cranking amps for Trucks & S U V's will be permitted.
- **6. NO REINFORCEMENTS OF ANY KIND WILL BE ALLOWED.** Only exception will be the driver side front & passenger side front door,(IT is recommended that both drivers & passenger side door be reinforced with steel bar / angle iron / or pipe. Length not to extend past 8 inches on either side of doors vertical seam). You may weld the rear end differentials to create a positive traction rear end. It is suggested that you attach two vertical metal rods or chains 12 inches from each end of the windshield opening to protect driver from hood coming off of hinges. Trailer hitches or any type of stiffening device are considered reinforcements. Welding of bumper shocks are considered reinforcements. **Mini Trucks-** you may create **roll over bars on the interior of the cab** (to prevent top of cab collapsing). No exterior HALO Bars. Truck beds(See Number 7) Maximum Mini-Truck bumper height of 22 inches height from center of bumper for compact trucks. You must place some type of screen in two door pick-ups back glass opening to prevent arms or head from extending from the opening. It is suggested to pad drivers side doors & rig a head rest or padding behind all two door truck seats to protect the driver.
- 7. STANDARD EXHAUST SYSTEM may be removed or cut off just aft of the fire wall. NOT PERMITTED: additional headers, stacks, custom manifolds that protrude above the level of the hood more than 16" or extend past the body of the vehicle or through the interior of the vehicle. DO NOT WELD OR BOLT hoods down. Use wire. All doors must be chained shut or secured with wire (wire is preferred on at least one door to allow for quick removal of injured participants). If a driver's side door comes open, he or she will be disqualified. If doors are welded, a maximum of 2- four inch welds in length on 2- vertical seams per door will be permitted. Truck tail gates must be factory or none at all. Factory tailgate must be welded shut with a maximum of four 4" inch welds. Factory Pick-up Beds only. No wooden, steel flat beds, or dump beds allowed. You are permitted to fasten the truck bed down with eight additional fasteners or four inch welds. You may weld the steering sectors. You must cover the back cab window with some type of screen and place at least two vertical hood bars within the windshield opening. (To prevent hood from coming in on driver.) You should place a vertical bar/post running from the floor board to the top of the cab bolted from inside out near the center of the back window. The post should be strong enough to act as a brace if you should go inverted on your top. Bumpers must be stock only. No Commercial bumpers, car bumpers, wooden bumpers, or home made fabricated bumpers. No tow hitches, brush guards, or running boards.
- 8. ALL FAN BLADES must be removed. Only exception will be if your vehicle is equipped with a slip clutch fan blade and fan shroud or came stock with an electric fan and shroud. You may add on one (1) electrical fan or additional transmission cooler. Transmission coolers must stay under the hood. If your vehicle is missing a fan shroud you may create your own shroud with some type of thin metal. Do not alter slip clutch fans in any method to prevent them from slipping as designed.
- 9. A 12 BY 15 INCH HOLE must be cut into the center of hood to allow for early fire detection.
- 10. PRIOR TO BRINGING VEHICLES TO FAIRGROUND radiators must be drained and back flushed of all antifreeze coolants. They then can be refilled with water, or the new naturally biodegradable animal friendly coolant. Disconnect & discharge all Air Bag Systems. Disconnect, discharge & remove all air conditioning refrigerant system. You may leave serpentine belts that keep your charging system intact
- 11. SAFETY BELTS, HELMETS, AND IMPACT RESISTANT EYE PROTECTORS are required. If car was equipped with a shoulder restraint system including lap belt, use both. Driver can be disqualified at any time if either belt or helmet is removed during a heat. Long sleeve-shirts & pants should be worn. We suggest that you consider wearing Fire Retardant coveralls or clothing.
- 12. THE DERBY WILL BE COMPOSED OF A Specialty heat for Mini Pickups, Mini S u v's & 4 Cyl Cars. Cash prizes and trophies to each heat winner. Winners of the Specialty heat will be awarded a spot in the 4 Cyl feature heat. The shows designated Best Appearance Theme: Is denoted on the entry blank and pertains to both Mini Trucks, Mini S U V's Vehicles and 4 Cyl Cars.
- 13. ADDITIONAL SAFETY REGULATIONS MAY BE IMPOSED depending on the track. Rules are subject to change to fit event. If you have any safety concerns, Call 1-865-382-1955. Just because it is not stated in the rules does not make it allowable. you have Doubts or Questions call.

 THE DECISION OF JUDGE IS FINAL. ANY DRIVER NOT OBEYING THE RULES WILL BE DISQUALIFIED.

If you have any doubts about the Vehicles capability of use for this event call # 1-865-382-1955.